



# DuraLabel BRONCO<sup>®</sup> MAX



- Quick-load ribbon cartridges
- Print high-quality, easy-to-read signs and labels
- Built-in Ethernet port allows for easy network printing
- Industry-leading label design software included
- Lifetime customer service included

## SPECIFICATIONS

### PRINT MECHANISM

- Type: Thermal Transfer
- Print Speed: up to 3" per second
- Resolution: 300 dots per inch
- Max. Print Width: 4.0"
- Max. Print Length: 120"
- Cutter: Automatic

### INTERFACE

- Buttons: Power, Supply Feed
- Communications:  
USB 2.0 (USB-B), Ethernet

### POWER REQUIREMENTS

- Power to Printer (from AC Adapter):  
24 VDC, 6.25A
- Power to AC Adapter: 100 – 240  
VAC, 50 – 60 Hz, 2.8A (max)
- Different AC adapters available for  
worldwide usage

### OPERATING ENVIRONMENT

- Operating Temperature:  
41°F – 104°F (5°C – 40°C)
- Operation Humidity:  
30% – 85%, non-condensing
- Storage Temperature:  
-4°F – 122°F (-20°C – 50°C)
- Storage Humidity:  
10% – 90%, non-condensing

### LABEL STOCK

- Types: Continuous, Black Mark,  
and Die-Cut
- Width: 0.20" minimum, 4"  
maximum
- Gap/Mark Height: 0.12"
- Capacity: varies by supply; external  
feed available

### RIBBON SUPPLY

- Width: 106 mm (4.17")
- Capacity: 360'
- Type: Wax/resin, resin

### PRINTER BODY

- Dimensions:  
13.5"W x 10.25"D x 8.5"H
- 12.5 lbs (5.67 kg), excluding  
supplies

*Bronco Max specifications are  
subject to change without notice.*



## MAXIMIZE YOUR SAFETY PROGRAM

COLIVARES@MESSOCONSULTORES.COM | WWW.MESSOCONSULTORES.COM

