

## Fixing accessories



### M12 - M16

HILTI

Hole required  $\varnothing$  12-16  
Galvanized steel.



### S12 - S12X150 - S16

HILTI

Hole required  $\varnothing$  10-10-14  
Galvanized steel.



### B12 - B16 - B20

HILTI

Hole required  $\varnothing$  22-28-32  
Galvanized steel.



### S8FH - S12FH

HILTI

Hole required  $\varnothing$  6-10  
Galvanized steel.  
Countersunk.



### SF12 - SF16 - SF20 INOX

Hole required  $\varnothing$  14-18-24  
Stainless steel.



### M12 - M16 INOX

Hole required  $\varnothing$  12-16  
Stainless steel.



### KIT ROD 70-120

HILTI

Hole required  $\varnothing$  38-56  
Galvanized steel.



### KIT ROD 70-120 INOX

HILTI

Hole required  $\varnothing$  38-56  
Galvanized steel.



### AA12 - AA16

Hole required  $\varnothing$  22-22  
Galvanized steel.  
For asphalt.



### ASPHALT CHEMICAL

CHEMICAL ANCHOR  
385 ML



### FR

HILTI CHEMICAL ANCHOR  
300 ML



### WIT NORDIC

CHEMICAL ANCHOR  
420 ML

(Installation in working cold rooms  
with negative temperatures)

In collaboration with



MPM srl reserves the right, at any time, to introduce the necessary changes and improvements to its products. Any small imperfection in the products and in the materials used are due to the processing method. Any reproduction of this brochure, even in part, is forbidden.

**TM5**  
Hole required Ø 8.5  
Neutral polyethylene. 100/500 Pcs. / bag.

**TS9**  
Hole required Ø 5  
White or grey nylon. 1000 Pcs. / bag.

**TB14 - TB20**  
Hole required Ø 4-5  
Steel / aluminium (white for ø 4)  
500 Pcs. / box.

**TF14 - TF20**  
Hole required Ø 5-6.5  
Aluminium. 500 Pcs. / box.

**FIX P90**  
Galvanized steel and painted.

**COVER 90 RE**  
Galvanized steel and painted.

**FIX P90 INOX**  
Stainless steel.

**FIX P150**  
Galvanized steel and painted.

**COVER 150 RE**  
Galvanized steel and painted.

**FIX P150 INOX**  
Stainless steel.

**FIX P150 FH**  
Galvanized steel and painted.  
Countersunk.

**FULL FRAME BASE**  
Galvanized steel and painted.

**SHOCK ABSORBER PAD**  
Soft material, optional for FIXP150.  
(To be installed with S12x150)

## Colours



MPM srl reserves the right, at any time, to introduce the necessary changes and improvements to its products.  
Any small imperfection in the products and in the materials used are due to the processing method.  
Any reproduction of this brochure, even in part, is forbidden.